

CI-3100 OPT Series Remote Particle Counters Internal Vacuum Pump 1 CFM Continuous Monitoring When Accuracy Matters! TM

For Continuous Monitoring and
Systems Integration

High Accuracy & Assurance

Stainless Steel Enclosure

VHP Compatible

HEPA Filtered Exhaust On
Most Models

Easy To Install, Operate and
Validate

Automatic Flow Control

Remotely Controlled and
Monitored

Connects to existing network
infrastructure and a variety of
data logging or standard
environmental monitoring
systems including LIMS
Software.

ISO 21501-4

ISO 14644-1

EU GMP, Annex 1

FS-209E

JIS 9921

21 CFR Part 11



Unsurpassed ease of use
and reliability. The **CI-3100**

OPT Series is designed for
continuous monitoring, and offers users a choice of standard data interface
options including Ethernet Modbus and 4-20 mA outputs.

Reliability, Accuracy & Support

The **CI-3100 Series** of particle counters are engineered and manufactured with only the highest quality materials. This ensures a long product life-cycle, and up to decades of reliable use. Moreover, we provide calibration support services for all our instruments over their lifetime. We have built our reputation by providing highly accurate instruments that stand the test of time. Climet internal audits confirm that units returned for calibration have an "In Tolerance" rate of more than 98%. This study includes some units that have been manufactured more than 20 years ago. Simply, Climet particle counters are designed, tested, and calibrated with very tight tolerances to exceed industry standards. Years of count efficiency testing has demonstrated that a properly calibrated Climet particle counter produces good count efficiency even after more than a decade of field operation!

Return On Investment

Not all particle counters are equal. The initial purchase price, cost of calibrations, cost of consumables, out of warranty repairs, and product life-cycle all factor into calculating the Return on Investment. Other intrinsic factors include assurance, reliability, accuracy, application support, and superior customer service. These make Climet the unsurpassed leader in the manufacture of particle counters for cleanroom monitoring, validation, and certification.

Custom Engineered Solutions

If you have a specific technical requirement, please contact us. We specialize in customizing our products to fit your needs.

Applications Include:

Cleanroom Monitoring & Validation
Medical Device Manufacturing
Pharmaceutical Manufacturing
Hospitals

Food & Beverage Processing
Aerospace Assembly
Pharmaceutical Compounding
Cosmetic Manufacturing

CLIMET[®]
INSTRUMENTS COMPANY

CI-3100 OPT Series Specifications

Performance	<p>Flow Rate Control: Electronic, automatic closed loop</p> <p>Particle Channel Sizes: 0.3, 0.5, or 5.0 microns on 2-channels (please contact us for other size requirements)</p> <p>Concentration Limit:</p> <p>0.1 CFM: 10.0 x 10⁶ particles per cubic foot (353 x 10⁶ particles per cubic meter) @ 10% coincidence</p> <p>1.0 CFM: 1.0 x 10⁶ particles per cubic foot (35.3 x 10⁶ particles per cubic meter) @ 10% coincidence</p> <p>Resolution: Exceeds requirements of ISO 21501-4 of 15% (4-10% typical)</p> <p>Count Efficiency: 50% Count Efficiency exceeds ISO 21501-4 of ±20% (≤±10% typical)</p> <p>100% Count Efficiency @ ±10% per ISO 21501-4</p> <p>Max. False Count: 1.00 CFM: 7.1 / CM (95% UCL) per ISO 21501-4</p> <p>0.10 CFM: 71 / CM (95% UCL) per ISO 21501-4</p> <p>Optics: Rhodium plated metal ellipsoidal mirror (extreme durability and resistant to contamination)</p> <p>Laser Diode: Optimal balance of long life, stability and resolution for added accuracy.</p> <p>Cleaning: Compatible with common cleaning and sterilization procedures, including VHP</p> <p>Vacuum Source: Power efficient internal vacuum source</p>
Accessories Included	Zero count filter, IQ/OQ Docs, manual, and external exhaust fitting (on select models)
Other Accessories Available	Stainless steel isokinetic probes, tubing, probe stands, high pressure diffusers, software, validation documentation, customized cabling, and other accessories sold separately.
LED Status Indicators	Power, Alarm, Count, Laser Status, and Flow Status
Environmental	<p>Operating temperature: 0-36° C, 32-97° F</p> <p>Dimensions: 6" (W) x 4" (H) x 11.5" (D) (15.24 cm x 10.16 cm x 29.21 cm)</p> <p>0-90% relative humidity, non-condensing</p>
Compliance	ISO 21501-4; ISO 14644-1; EU GMP, Annex 1; FS-209E; JIS 9921; and FDA 21 CFR Part 11 with software

CI-3100 - _____ **- OPT**

Interface Voltage Size Sensitivity Flow Rate

INTERFACE OPTIONS

- 12*** = 4-20 mA Signal Output Stainless Steel Case
- 14*** = Device Net Interface
- 21*** = Ethernet Modbus w/ Built-in Webpages Viewed via Web

Browser

- 22*** = RS-485 Modbus

VOLTAGE OPTIONS

- 0 = External Power, 24 VDC
- 1 = 115 VAC USA
- 2 = 230 VAC EURO
- 3 = 230 VAC UK
- 8 = 230 VAC EURO, Remote power option and flow rate output

SIZE SENSITIVITY OPTIONS

- 4*** = 0.5 / 5.0 µm
- 6 = 0.3 / 0.5 µm

FLOW RATE OPTIONS

- 2 = 0.10 CFM
- 4*** = 1.00 CFM
- 6*** = 1.00 CFM with External Exhaust
- 7 = 0.10 CFM with External Exhaust

*** = most popular versions.**

Climet Instruments Company

1320 West Colton Ave
Redlands, CA 92374 (USA)
Tel: +1 (909) 793-2788

www.climet.com | sales@climet.com

