

The General Purpose Manual Defrost Freezers are intended for general purpose applications where precise temperature control and maintenance are not essential and there are no requirements for temperature alarms. Manual defrost units have been designed to operate without product damaging auto defrost cycles.

Periodic manual defrosting is required.

FEATURING

- Mechanical thermostat
- Adjustable temperature range: -15°C to -25°C
- Manual defrost
- Keyed door lock
- Magnetic door gasket for positive seal
- Heavy duty door handle
- Leveling legs
- Probe access port
- Casters (2 ¾") with interchangeable leveling legs (15 ft³ only)
- CFC-free refrigerant, foam insulation and packaging
- UL/C-UL listed (30 ft³ only)
- One year parts and labor warranty, plus an additional four year compressor parts warranty




DAI-MFB-30



DAI-MFB-15-C



Environmentally friendly, natural hydrocarbon (HC) refrigerants that vastly reduce global-warming potential while meeting new EPA/SNAP mandates. (15ft³ only)

Freezer Model	Ft³	Set Point	Defrost	Doors	Shelves	Width"	Depth"	Height"
DAI-MFB-30	30	-20°C	Manual	1 Solid	4 Fixed	35 ¾	34 ¼	72 ½
Chest Freezer Model	Ft³	Set Point	Defrost	Doors	Shelves	Width"	Depth"	Height"
 DAI-MFB-15C	15	-20°C	Manual	1 Hinge	2 Baskets	56	29 ½	35 ⅝†

Specifications are subject to change

†Height includes 2 ¾" casters