

The Basic Pharmacy Refrigerators feature a digital microprocessor temperature controller allowing for the precise temperature management necessary for critical samples and supplies. A forced air directional refrigeration system provides superior temperature uniformity and recovery after door openings. An automatic cycle-defrost design prevents product damaging temperature spikes.

### FEATURING

- Microprocessor temperature controller
- Adjustable temperature range: 36°F to 46°F (2°C to 8°C)
- Remote alarm contacts
- Back wall evaporator cover
- Forced draft circulation
- Keyed door lock
- Magnetic door gasket for positive seal
- Swivel Casters (3 1/2")
- LED interior lights are safety shielded and switch controlled
- Probe access port
- Vaccine storage power cord warning label
- Pharmacy refrigerator/freezer toolkit with temperature logs
- Temperature Monitor Device - complies with the current CDC guidelines, 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory, °F/°C switchable, field installable, and visual & audible temperature alarms
- Pyxis®, Omnicell® and AcuDose RX® compatible
- ETL Listed
- One year parts and labor warranty, plus an additional four year compressor parts warranty



PH-DAI-HC-S16G

PH-DAI-HC-S36S






















**PH-DAI-HC-S49S**



- Digital temperature display
- Audible and visual temperature alarms
- Resettable Min/Max
- °C/°F switchable



Environmentally friendly, natural hydrocarbon (HC) refrigerants that vastly reduce global-warming potential while meeting new EPA/SNAP mandates.

Glass Door Model	Ft <sup>3</sup>	Set Point	Defrost	Doors	Shelves	Width"	Depth"	Height"
 PH-DAI-HC-S12G	12	41°F	Cycle	1 Swing Glass	3 Adj.	25	29 ¾"	65 ¾"
 PH-DAI-HC-S16G	16	41°F	Cycle	1 Swing Glass	3 Adj.	25	29 ¾"	79"
 PH-DAI-HC-S23G	23	41°F	Cycle	1 Swing Glass	4 Adj.	26 7/8"	34 ¾"	81 ¾"
 PH-DAI-HC-S26G	26	41°F	Cycle	1 Swing Glass	4 Adj.	28 3/8"	36 ½"	81 ¾"
 PH-DAI-HC-S33G	33	41°F	Cycle	2 Sliding Glass	8 Adj.	39 5/8"	33 ¼"	81 ¾"
 PH-DAI-HC-S36G	36	41°F	Cycle	2 Swing Glass	8 Adj.	39 5/8"	34 ¾"	81 ¾"
 PH-DAI-HC-S47G	47	41°F	Cycle	2 Sliding Glass	8 Adj.	54 1/8"	33 ¼"	81 ¾"
 PH-DAI-HC-S49G	49	41°F	Cycle	2 Swing Glass	8 Adj.	54"	34 ¾"	81 ¾"
 PH-DAI-HC-S69G	69	41°F	Cycle	3 Sliding Glass	12 Adj.	81"	33 ¼"	81 ¾"
 PH-DAI-HC-S72G	72	41°F	Cycle	3 Swing Glass	12 Adj.	81"	34"	81 ¾"
<b>Solid Door Model</b>								
 PH-DAI-HC-S12S	12	41°F	Cycle	1 Swing Solid	3 Adj.	25	29 ¾"	65 ¾"
 PH-DAI-HC-S16S	16	41°F	Cycle	1 Swing Solid	3 Adj.	25	29 ¾"	79"
 PH-DAI-HC-S23S	23	41°F	Cycle	1 Swing Solid	4 Adj.	26 7/8"	34 ¾"	81 ¾"
 PH-DAI-HC-S26S	26	41°F	Cycle	1 Swing Solid	4 Adj.	28 3/8"	36 ½"	81 ¾"
 PH-DAI-HC-S36S	36	41°F	Cycle	2 Swing Solid	8 Adj.	39 5/8"	34 ¾"	81 ¾"
 PH-DAI-HC-S49S	49	41°F	Cycle	2 Swing Solid	8 Adj.	54"	34 ¾"	81 ¾"
 PH-DAI-HC-S72S	72	41°F	Cycle	3 Swing Solid	12 Adj.	81"	34"	81 ¾"

Specifications are subject to change

\*Height includes 3 ½" casters