

The Plus Series Compact Laboratory Refrigerators feature a microprocessor temperature controller and display, allowing for precise temperature control, verification and recovery versus mechanical style thermostats.

An interior fan driven, forced-draft air circulation system provides excellent temperature uniformity and recovery after door openings. Critical samples and supplies are security backed with an extensive package of audible and visual alarms.



DAI-HC-10G

DAI-HC-10S

FEATURING



- Microprocessor temperature controller
- Adjustable temperature range: 1°C to 10°C
- Cycle defrost
- Remote alarm contacts
- Forced draft air circulation
- Keyed door lock
- Magnetic door gasket for positive seal
- Leveling legs
- Recessed door handle
- LED interior lights
- Probe access port
- UL/C-UL listed
- Two year parts and labor warranty, plus an additional three year compressor parts warranty
- These models require 4" of clearance around back and sides of the unit for proper ventilation. Improper installation will void the warranty and will lead to temperature maintenance issues, overheating and possible failure



- Digital temperature display
- Audible and visual temperature alarms
- Resettable Min/Max
- °C/°F switchable



Environmentally friendly, natural hydrocarbon (HC) refrigerants that vastly reduce global-warming potential while meeting new EPA/SNAP mandates.

Glass Door Model	Ft ³	Set Point	Defrost	Doors	Shelves	Width"	Depth"	Height"
 DAI-HC-10G	10.5	4°C	Cycle	1 Glass	6 Adj.	23 ¾	26 ½	59
Solid Door Model								
 DAI-HC-10S	10.5	4°C	Cycle	1 Solid	6 Adj.	23 ¾	26 ½	59

Specifications are subject to change