

The Plus Series Stainless Steel Refrigerators feature a microprocessor temperature controller allowing for the precise temperature management necessary for critical samples and supplies.

The temperature display and alarm module offers product security with a monitoring and alarm system. Real-time sample simulated temperatures are constantly displayed and supported by audible/visual high and low temperature alarms. Remote alarm dry contacts and an access port are provided to simplify connections to existing facility monitoring systems.



DAI-HC-SSP-49G

FEATURING



- Microprocessor temperature controller
- Adjustable temperature range: 1°C to 10°C
- Cycle Defrost
- Remote alarm contacts
- Forced draft air circulation
- Keyed door lock
- Magnetic door gasket for positive seal
- LED interior lights
- Swivel casters (5 3/4")
- Probe access port
- ETL Listed
- Two year parts and labor warranty, plus an additional three year compressor parts warranty



- Digital temperature display
- Audible and visual temperature alarms
- Resettable Min/Max
- °C/°F switchable



Environmentally friendly, natural hydrocarbon (HC) refrigerants that vastly reduce global-warming potential while meeting new EPA/SNAP mandates.

Glass Door Model	Ft ³	Set Point	Defrost	Doors	Shelves	Width"	Depth"	Height"
 DAI-HC-SSP-23G	23	4°C	Cycle	1 Glass	4 Adj.	26 3/4	35 3/4	83 1/4*
 DAI-HC-SSP-49G	49	4°C	Cycle	2 Glass	8 Adj.	54	35 3/4	83 1/4*
 DAI-HC-SSP-72G	72	4°C	Cycle	3 Glass	12 Adj.	81	35 3/4	83 1/4*
Solid Door Model								
 DAI-HC-SSP-23	23	4°C	Cycle	1 Solid	3 Adj.	26 3/4	34 7/8	83 7/8*
 DAI-HC-SSP-49	49	4°C	Cycle	2 Solid	6 Adj.	54	35 3/4	83 1/4*
 DAI-HC-SSP-72	72	4°C	Cycle	3 Solid	12 Adj.	81	35 3/4	83 1/4*

Specifications are subject to change
*Height includes 5 3/4" casters