

Product Name:	CRT-DAI-HC-10PS
Description:	Plus Series Upright Controlled Room Temperature Cabinet, Solid Door 10.5 Cu. Ft. Capacity One solid swing door, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms 2 probes; 1 in air and 1 in sample bottle Remote alarm contacts Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) Calibrated using a NIST traceable device, three year certificate included Six adjustable shelves with guard rail on back to prevent product from being pushed against back wall Bottom footed shelf to allow air circulation Back wall evaporator cover Vaccine storage power cord warning label Forced draft circulation Keyed door lock ,magnetic door gasket for positive seal Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet insulation HFC-free refrigerant (R600a), foam insulation and packaging Vaccine toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾"W x 26 ½"D x 59"H <i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i> UL/C-UL listed Cycle defrost ENERGY STAR CERTIFIED 115V, 60 Hz, 1/3 HP, 2.3 Amps

Shipping weight: 183 lbs.