

Product Name:	CRT-ABT-HC-S12G
Description:	<p>Plus series Upright Controlled Room Temperature Cabinet, Glass Door</p> <p>12 Cu. Ft. Capacity</p> <p>One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged, not reversible</p> <p>Microprocessor temperature controller</p> <p>Digital temperature display</p> <p>Audible and visual high and low temperature alarms</p> <p>Remote alarm contacts</p> <p>Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)</p> <p>Calibrated using a NIST traceable device, three year certificate included</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Three adjustable shelves</p> <p>Vaccine storage power cord warning label</p> <p>Forced draft air circulation</p> <p>Keyed door lock</p> <p>Magnetic door gasket for positive seal</p> <p>Heavy duty door handle</p> <p>Swivel Casters (3")</p> <p>LED interior lights are safety shielded and switch controlled Probe access port ($\frac{3}{8}$")</p> <p>Powder coated steel white interior and exterior</p> <p>High density urethane foam cabinet insulation</p> <p>Hydrocarbon, natural refrigerant (R290)</p> <p>One year parts and labor warranty, plus an additional four year compressor parts warranty</p> <p>Exterior dimensions: 25" W x 29 $\frac{3}{4}$" D x 65 $\frac{3}{4}$" H with casters; 62 $\frac{1}{4}$" H without casters</p> <p>Cycle defrost</p> <p>115V, 60 Hz, 3 Amps, 1/5 HP</p> <p>ETL listed</p> <p>Shipping weight: 258 lbs.</p>