

Product Name:	CRT-DAI-HC-S26S
Description:	<p>Plus Series Upright Controlled Room Temperature Cabinet, Solid Door</p> <p>26 Cu. Ft. capacity</p> <p>One swing solid door, self-closing, right hinged, not reversible Microprocessor temperature controller</p> <p>Digital temperature display</p> <p>Audible and visual high and low temperature alarms</p> <p>Remote alarm contacts</p> <p>Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Calibrated using a NIST traceable device, three year certificate included</p> <p>Four adjustable shelves</p> <p>Vaccine storage power cord warning label</p> <p>Forced draft air circulation</p> <p>Keyed door lock</p> <p>Magnetic door gasket for positive seal</p> <p>Heavy duty door handle</p> <p>LED interior lights are safety shielded and switch controlled Swivel Casters (3")</p> <p>Probe access port ($\frac{3}{8}$")</p> <p>White powder-coated steel exterior and interior</p> <p>Hydrocarbon, natural refrigerants (R290)</p> <p>One year parts and labor warranty, plus an additional four year compressor parts warranty</p> <p>Exterior dimensions: 28 $\frac{3}{8}$" W x 36 $\frac{1}{2}$" D x 81 $\frac{3}{4}$" H with casters; 78 $\frac{1}{4}$" H without casters</p> <p>Cycle defrost</p> <p>115V, 60 Hz, 3 Amps, 1/5 HP</p> <p>ETL listed</p> <p>ENERGY STAR CERTIFIED</p> <p>Shipping weight: 275 lbs.</p>