

Product Name:	CRT-DAI-HC-UCBI-0204-LH
Description:	Plus Series Undercounter Controlled Room Temperature Cabinet, Built-In 2.5 Cu. Ft. Capacity One solid swing door, left hinged Microprocessor temperature controller Digital temperature display Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Calibrated using a NIST traceable device, three year certificate included Four adjustable shelves (two large, two small) with guard rail on back to prevent product from being pushed against the back wall Back wall evaporator cover Vaccine storage power cord warning label Self-closing door Forced draft circulation Keyed door lock Magnetic door gasket for positive seal Leveling legs LED light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis[®], Omnicell[®] and AcuDose RX[®] compatible Exterior dimensions: 17 3/4"W x 22 3/4"D x 30 3/4"H Cycle defrost 115V, 60 Hz, .90 Amps, 1/8 HP ADA compliant UL/C-UL listed Shipping weight: 85 lbs.