

Product Name:	CRT-DAI-HC-UCBI-0404
Description:	Plus Series Undercounter Controlled Room Temperature Cabinet, Built-In 4.6 Cu. Ft. Capacity One solid swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Calibrated using a NIST traceable device, three year certificate included Adjustable operating temperature range: 68°F–77°F (20°C – 25°C) Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from being pushed against the back wall Back wall evaporator cover Vaccine storage power cord warning label Forced draft circulation Recessed door handle Keyed door lock Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾ "W x 24 ½" D x 33 3/8 "H Cycle defrost 115V, 60 Hz, 1/8 HP, 1.74 Amps UL/C-UL listed ENERGY STAR CERTIFIED Shipping weight: 137lbs.