

Product Name:	CRT-DAI-HC-UCFS-0204
Description:	<p>Plus Series Undercounter Controlled Room Temperature Cabinet, Freestanding 2.5 Cu. Ft. Capacity</p> <p>One solid swing door, right hinged, not reversible</p> <p>Microprocessor temperature controller</p> <p>Digital temperature display</p> <p>Adjustable operating temperature range: 68°F–77°F (20°C – 25°C)</p> <p>Audible and visual high and low temperature alarms</p> <p>Remote alarm contacts</p> <p>2 probes; 1 in air and 1 in sample bottle</p> <p>Calibrated using a NIST traceable device, three year certificate included</p> <p>Four adjustable shelves (two large, two small) with guard rail on back to prevent product from being pushed against the back wall</p> <p>Back wall evaporator cover</p> <p>Vaccine storage power cord warning label</p> <p>Forced draft circulation</p> <p>Keyed door lock</p> <p>Magnetic door gasket for positive seal</p> <p>Leveling legs</p> <p>LED light</p> <p>Probe access port (3/8")</p> <p>Powder coat exterior</p> <p>High density urethane foam cabinet and door insulation</p> <p>HFC-free refrigerant (R600a), foam insulation and packaging</p> <p>Two year parts and labor warranty, plus an additional three year compressor parts only warranty</p> <p>Pyxis®, Omnicell® and AcuDose RX® compatible</p> <p>Exterior dimensions: 17 3/4"W x 19 1/2"D x 28 7/8"H</p> <p><i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i></p> <p>Cycle defrost</p> <p>115V, 60 Hz, .90 Amps, 1/8 HP</p> <p>ADA compliant</p> <p>UL/C-UL listed</p> <p>ENERGY STAR CERTIFIED</p> <p>Shipping weight: 85 lbs.</p>