Description: PH-DAI-HC-12G Plus Series Pharmacy/Vaccine Glass Door Refrigerator 12 Cu. Ft. capacity One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Calibrated using a NIST traceable device, three year certificate included 2 probes; 1 in air and 1 in sample bottle Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back 5 total shelves, 3 adjustable plus 2 additional Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Swivel Casters (3 ½") LED interior lights are safety shielded and switch controlled Probe access port (%") Powder coated steel white interior and exterior Hydrocarbon, natural refrigerant (R290)	i i loduct mailic. i	PH_DALHC_12G
12 Cu. Ft. capacity One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Calibrated using a NIST traceable device, three year certificate included 2 probes; 1 in air and 1 in sample bottle Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back 5 total shelves, 3 adjustable plus 2 additional Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Swivel Casters (3 ½") LED interior lights are safety shielded and switch controlled Probe access port (%") Powder coated steel white interior and exterior		1 11-DAI-110-120
Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 25" W x 29 ¾" D x 65 ¾" H with casters; 62 ¼" H without casters Cycle defrost 115V, 60 Hz, 3 Amps, 1/5 HP ETL listed Shipping weight: 258 lbs	Description:	12 Cu. Ft. capacity One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Calibrated using a NIST traceable device, three year certificate included 2 probes; 1 in air and 1 in sample bottle Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back 5 total shelves, 3 adjustable plus 2 additional Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Swivel Casters (3 ½") LED interior lights are safety shielded and switch controlled Probe access port (¾") Powder coated steel white interior and exterior Hydrocarbon, natural refrigerant (R290) Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 25" W x 29 ¾" D x 65 ¾" H with casters; 62 ¼" H without casters Cycle defrost 115V, 60 Hz, 3 Amps, 1/5 HP ETL listed