

Product Name:	PH-DAI-HC-RFC12GA-CAD
Description:	<p>Plus Series Pharmacy/Vaccine Refrigerator & Freezer Combination with Controlled Auto Defrost Freezer 12 Cu. Ft. capacity (10.5 Ref./1.0 Freezer) Two exterior swing doors (glass door refrigerator/solid door freezer), right hinged, not reversible Microprocessor temperature controller, refrigerator and freezer Digital temperature display with sample simulated probe, refrigerator and freezer Adjustable operating temperature range: Refrigerator: 36°F - 46°F (2°C - 8°C) Freezer: 5°F – -13°F (-15°C – -25°C) Defrost: Auto defrost cycle every 6 hours: (at Set Point -11°F /-24°C) Max air temp in empty freezer: 5°F (-15°C) Max air temp in loaded freezer: 3°F (-16°C) Max sample temp in empty freezer: 0°F (-18°C) Max sample temp in loaded freezer: -4°F (-20°C) Calibrated using a NIST traceable device, three year certificate included Remote alarm contacts, refrigerator and freezer Six adjustable shelves with guard rail on back to prevent product from being pushed against back wall, Refrigerator Two adjustable shelves with guard rail on back to prevent product from being pushed against back wall, Freezer Bottom footed shelf to allow air circulation, Refrigerator and Freezer Vaccine storage power cord warning label Forced draft circulation Refrigerator Keyed door locks Magnetic door gasket for positive seal Integrated door handles Leveling legs Stacking kit Two probe access ports (3/8"); one, refrigerator/one, freezer White powder coated exterior HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts warranty</p> <p>Pyxis[®], Omnicell[®] and AcuDose RX[®] compatible Exterior dimensions: 23 3/4" W x 26 1/2" D x 80 1/4" H Controlled Auto Defrost freezer, Patented Technology Cycle defrost refrigerator 115V, 60 Hz, 2.3 Amps refrigerator, 1 Amp freezer, 1/3 HP refrigerator, 1/8 HP freezer</p>

	<p>UL/C-UL listed Shipping weight: 316 lbs. In stock, with next day shipping *Please note this unit requires 2 outlets.</p>
--	--